

VinaGARD® 51-19

Heavy Duty Double Coated Protective Fabric

Product Features and Benefits

- unique extrusion coating process provides flexibility
- inherently flame retardant
- U.V. resistant for long life
- resists internal and external mildewing
- tear and abrasion resistant
- rot and fungus resistant
- high strength, low wick base fabric
- dielectrically and thermally weldable

Typical Physical Properties

Property:	Typical Test Results:	Test Method:
Total Weight (oz/yd ²):	19 oz	ASTM D 3776
Tear (lb):	68 (w) x 71 (f)	ASTM D1117
Tensile (lb/inch):	295 (w) x 271 (f)	ASTM D751
Adhesion (lb/inch):	11 (w) x 10 (f)	ASTM D751
Cold Crack (1/8" Mandrel):	-45°C	ASTM D2136 ASTM E 84 Class A FAR 25.583 (a)Vertical CAN/ULC-S109 L&S NFPA 701-1989 Large Scale CA1237.1 small CAN/CGSB-4.2#27.1
Flame Retardancy:	Pass	CAN/CGSB-4.2#27.1
Stock Width:	61 "	
Stock Roll:	50 Meters / 111 lbs.	

Recommended End Use Applications

- protective covers
- gymnasium mats and pads
- divider curtains
- stationary tarpaulins
- pool covers
- awnings
- gymnasium floor coverings
- many others

See reverse for information on our company and other product capabilities

This information is obtained by industry accepted test methods and represents typical data. It is for your general information only. There are no warranties expressed or implied. The information is furnished upon the condition that the people receiving it shall conduct their own tests to determine the suitability of our material for the particular application involved. The data shown are typical physical values, not a specification or a performance guarantee.

Stock Colors

- 202 Burgundy
- 227 Grey
- 411 White
- 413 Red
- 414 Blue
- 440 Yellow
- 452 Black
- 470 Olympic Green

Reference Vintex color key swatch for true color samples. VinaGARD® 51-19 is also available in custom colors, widths and embossing patterns.



ISO 9002 Registered

Customer Service Phone: 1-800-846-8399
Customer Service Fax: 1-888-256-0004

Rev: Jan 15/02
TPP# 0001