

# VinaGARD<sup>®</sup> 51-22

Stock Colors

## High Strength Double Coated Protective Fabric

### Product Features and Benefits

- tear and abrasion resistant
- inherently flame retardant
- U.V. resistant for long service life
- resists internal and external mildewing
- rot and fungus resistant
- dimensionally stable and shrink resistant
- Dielectrically and thermally weldable
- excellent low temperature properties

### Typical Physical Properties

Property:	Typical Test Results:	Test Method:
Total Weight (oz/yd <sup>2</sup> ):	22 oz	ASTM D 3776
Tear (lb):	69 (w) x 67 (f)	ASTM D1117
Tensile (lb/inch):	294 (w) x 269 (f)	ASTM D751
Adhesion (lb/inch):	11 (w) x 11 (f)	ASTM D751
Cold Crack (1/8" Mandrel):	-45°C	ASTM D2136
Flame Retardancy:	Pass	ASTM E84 Class A FAR 25.853(a) Vertical CAN/ULC-S109 NFPA 701-1999 Test 2 CA1237.1 small
Stock Width:	61"	
Stock Roll:	50 Meters / 130 lbs.	

Blue

Red

Beige

Dark Green

Light Grey

### Recommended End Use Applications

- protective covers
- gymnasium mats and pads
- divider curtains
- stationary tarpaulins
- pool covers
- awnings
- gymnasium floor coverings
- many others

See reverse for information on our company and other product capabilities

This information is obtained by industry accepted test methods and represents typical data. It is for your general information only. There are no warranties expressed or implied. The information is furnished upon the condition that the people receiving it shall conduct their own tests to determine the suitability of our material for the particular application involved.

VinaGARD<sup>®</sup> 51-22 is also available in custom colors, widths and embossing patterns



ISO 9002 Registered

Customer Service Phone: 1-800-846-8399  
Customer Service Fax: 1-888-256-0004

Rev: Jan 15/02  
TPP# 0002